







## NOTES:

- .> .<del>`</del>
- HERMETICITY 1E(-8) STD CC/SEC @1ATM.
  FINISH (PLATING THICKNESS IN MICRO-INCHES)
  GLASS + KOVAR
  GOLD PL.50 MIN. OVER NICKEL PL.100 MIN.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.



TITLE

an INFINIT® brand

PECIFIED SIONS IN SIO	A SIZE		3000	××××	×				
ED LEADING DIMENSIONS ARE INCHES  IN [] ARE MILLIMETERS  CABLE LENGTH (L) TOLERANCES:  L \$ 12 [305] = +1 [25] - 0  12 [305] < L \$ 60 [1524] = +2 [51] / 0  60 [1524] < L \$ 120 [3048] = +4 [102] / 0  [120 [3048] < L \$ 300 [7620] = +6 [152] / 0  300 [7620] < L = +5%L / -0  WN ARE FOR REFERENCE ONLY.  DRAWN BY  ITEM NO.  FM 10	CAGE CODE 3FKR5	ALL DIMENSIONS S	=±.2 [5.08] FRACTION :±.02 [.51] ±1/32 :±.005[.13] ANGLES:			TOLERANCES:	DIMENSION		
M10	DRAWN BY K.DANG	HOWN ARE FOR REFERE			CABLE LENGTH (	NS IN [] ARE MILLIMETERS	CIFIED LEADING DIMENSIC		
THIRD-ANGLE PROJECTION  THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE ENPORMATION AND DESIGN IN THIS DOCUMENT IS THE ENPORTORY ALL RIGHTS RESERVED. SHEET  OF  N/A  SCALE  N/A  REV  A		NCE ONLY.	2 [305] = +1 [25] / -0 [1524] = +2 [51] / -0 [3048] = +4 [102] / -0 [7620] = +6 [152] / -0 20] < L = +5%L / -0			L) TOLERANCES:	"	ONS ARE INCHES	
NAMD SUMMENT SUMENT SUM							ф ф	THIRD-ANGLE PROJ	
	> >		1	ORPORATION. RVED.	YOF	Z Z	<del></del>	ECTION	