







NOTES:

- FINISH (PLATING THICKNESS IN MICRO-INCHES)
 BERYLLIUM COPPER.
 GOLD PL. 4 MIN. OVER NICKEL-PHOSPHORUS ALLOY PL. 80 MIN. OVER COPPER PL. 20MIN.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES



TITLE

| ⊳ | SIZE | ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY. | X = ±.02 XX = ±.02 XXX = ±.00 | | × + | | S S |
|-----------|-----------|--|---|--|--|--|--------------|
| သူ | CAGE CODE | | X=±.2 [5.08] FRACTIONS XX=±.02 [.51] ±1/32 XXX=±.005[.13] ANGLES±1 | | | TOLERANCES: CABLE LENGTH (L) TOLERANCES: | |
| 3FKR5 | DE | | | | | | DIMENSIO |
| | 무 | | | | NS E | | |
| K DANG | DRAWN BY | N ARE FOR REFERE | | | DIMENSIONS IN [] ARE MILLIMETERS | | |
| FM1016-10 | ITEM NO. | NCE ONLY. | 12 [305] < 1.5 60 [1824] = 2.5 [3] / -0 60 [1524] < 1.5 60 [1824] = 2.5 [3] / -0 120 [3048] < 1.5 120 [3048] = +4 [102] / -0 120 [3048] < 1.5 300 [7820] = +6 [182] / -0 300 [7820] < 1.5 +5%L / -0 | | | L) TOLERANCES: | 0 0 0 0 0 0 |
| | | SCALE | SHEET | FAIRVIE | 0 | | |
| _ | | | THE INFORMATION AND ESSIGN IN THIS DOCUMEN IS THE PROPERTY OF IN MICROWAVE CORPORAL ALL RIGHTS RESERVED 1 OF | | | | |
| | | N/A | 유 | WAVE O | HIS D | RMATIC | Д |
| Þ | REV | A | | FAIRVIEW MICROWAVE CORPORATION. ALL RIGHTS RESERVED. | DESIGN IN THIS DOCUMENT IS THE PROPERTY OF | ON AND | 4 |
| | | | | | | | |