

N MALE

BNC MALE

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT
ADMINISTRATION REGULATIONS, DIVERSION CONTRARY TO U.S., LAW PROHIBITED.

INJECT OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES



	XX X X X X X X X X X X X X X X X X X X			ONLESS OF HERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES	
ALL DIN	.2 [5.08] .02 [.51] .005 [.13]				TOLER
MENSIONS SHO	FRACTIONS ± 1/32 ANGLES ± 1°				ANCES:
WN ARE FOR REFERE	L ≤ 17 12 [305] < L ≤ 60 60 [1524] < L ≤ 120 120 [3048] < L ≤ 300 300 [766				CABLE LENGTH (
NCE ONLY.	2 [305] = +1 [25] / -0 [1524] = +2 [51] / -0 [3048] = +4 [102] / -0 [7620] = +6 [152] / -0 20] < L = +5%L / -0			L) TOLERANCES:	ON ARE INCHES
SCALE N/A	SHEET OF 1	FAIRVIEW MICROWAVE CORPORATION ALL RIGHTS RESERVED.	DESIGN IN THIS DOCUMENT	THE INFORMATION AND	THIND-PANGLE PROJECTION
		120 3048 < 1.5 300 7620 = +6 152 / -0 SHEET 300 7620 < L = +5%L / -0 1 MN ARE FOR REFERENCE ONLY. SCALE	12 13 25 15 24 132 25 25 25 25 25 25 25	L ≤ 12 [305] = +1 [25] / -0 12 [305] < L ≤ 60 [1624] = +2 [51] / -0 60 [1524] < L ≤ 120 [3048] = +4 [102] / -0 120 [3048] < L ≤ 300 [7620] = 66 [152] / -0 300 [7620] < L = +5%L / -0 WAN ARE FOR REFERENCE ONLY.	CABLE LENGTH (L) TOLERANCES: L ≤ 12 [305] = +1 [25] /-0 12 [305] < L ≤ 60 [1624] = +2 [51] /-0 60 [1524] < L ≤ 120 [3048] = +4 [102] /-0 120 [3048] < L ≤ 300 [7620] = +6 [152] /-0 300 [7620] < L = +5%L /-0 WAN ARE FOR REFERENCE ONLY.

⊳

3FKR5

K.DANG

FMC00319