



5/8 HEX

11/16 FLATS

RG316

CONTACT

TNC FEMALE BULKHEAD

SNAP-ON MMBX PLUG RA

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES



TITLE

A 3FKR5	5	UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS TOLERANCES: CABLE LENGTH (L) TOLERANCES L \$ 12 [305] = +1 [25] XX = ± 02 [5.08] FRACTIONS XX = ± 02 [5.1] ± 1/32 XXX = ± 005[.13] ANGLES ± 1° 120 [3048] < L \$ 300 [7820] < L \$ 17820] = +6 [152] 300 [7820] < L \$ +5%L / 4
K DANG	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.	WISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS CABLE LENGTH (L) TOLERANCES: L ≤ 12 [305] = +1 [25] / -0 # 1/32 ANGLES ± 1° ANG
FMC.	NCE ONLY.	ADING DIMENSIONS ARE INCHES RE MILLIMETERS 2ABLE LENGTH (L) TOLEFANCES: L ≤ 12 [305] = +1 [25] / -0 12 [305] < L ≤ 60 [1824] = +2 [51] / -0 [1824] < L ≤ 120 [3048] = +4 [02] / -0 [3048] < L ≤ 300 [7620] = +6 [182] / -0 300 [7820] < L = +5%L / -0
EMCA1426	SCALE N/A	THIRD-ANGLE PROJECTION THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF FAIRNIEM MICROMANE CORPOPATION ALL RIGHT'S RESERVED. SHEET 1 OF 1
		-