



$\emptyset.400^{+.005}_{-.000}$ $\left[10.16^{+0.13}_{-0.00}\right]^{-}$ **MOUNTING HOLE** $.367^{+.005}_{-.000}$ $\begin{bmatrix} 9.33^{+0.13}_{-0.00} \end{bmatrix}$

NOTES:

- CABLES 84" AND UNDER HAVE 1 LABEL CENTERED. CABLES OVER 84" HAVE 2 LABELS, ONE AT EACH END 12.0" FROM THE END OF THE CONNECTOR. 6" FROM CABLE END 1 PLACE FOR ALL LENGTHS OF CABLE.

 $\dot{\mathbf{N}}$

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES



TITLE

| ⊳ | SIZE | | 5 | < - | TOLERANCES: | 9 | |
|----------|-----------|--|--|---|-----------------------------|------------------------------|----------------------------------|
| ည | CAGE CODE | ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY. | X = ±.2 [5.08] XX = ±.02 [.51] (XX = ±.005[.13] | | | 5 F 081 | |
| 3FKR5 | | | X=±2 [5.08] FRACTIONS XX=±.02 [5.1] ±1/32 XXX=±.05[.13] ANGLES±1° 12 [3048] < L≤12 [3048] = +4 [20]/-0 120 [3048] < L≤120 [3048] = +4 [102]/-0 XXX=±.005[.13] ANGLES±1° 120 [3048] < L≤300 [7620] = +6 [152]/-0 300 [7620] < L=+5%L/-0 SHEET | | | ANCES: | DIMENSIONS IN [] ARE MILLIMETERS |
| K.DANG | DRAWN BY | | | | | CABL | IN [] ARE M |
| A G | |)R REFERE | 300 [76 | 05] < L ≤ 60 4] < L ≤ 120 | L ≤ 1 | ELENGTH | ILLIMETER: |
| | ITEM NO. | NCE ONLY. | 300 [7620] < L = +5%L/-0 | 12 [305] < L ≤ 60 [1524] = +2 [51] / -0 60 [1524] < L ≤ 120 [3048] = +4 [102] / -0 | L ≤ 12 [305] = +1 [25] / -0 | CABLE LENGTH (L) TOLERANCES: | 0 5 |
| FMCA2266 | | | %L/-0 | [25] / -0 | NCES: | <u>.</u> | |
| 2266 | | SCALE | THE DESK IS FAIRVIEW N ALL | | | | |
| | | N/A | 1 9F | W MICROWAVE CORPOR | DESIGN IN THIS DOCUMENT | THE INFORMATION AND | → |
| ⊳ | REV | Ά | <u> </u> | FAIRVIEW MICROWAVE CORPORATION. ALL RIGHTS RESERVED. | OCUMENT TY OF | DN AND | ф |
| | | | | | | | |