


2.2-5 MALE

## 2.2-5 FEMALE BULKHEAD



## NOTES:

- CABLES 84" AND UNDER HAVE 1 LABEL CENTERED. CABLES OVER 84" HAVE 2 LABELS, ONE AT EACH END 12.0" FROM THE END OF THE CONNECTOR. 6" FROM CABLE END 1 PLACE FOR ALL LENGTHS OF CABLE.

 $\dot{\mathbf{N}}$ 

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES



A		XXX = ± XXX
CAGE CODE	ALL DIN	UNLESS OTHE  TOLER  X = ±.2 [5.08]  XX = ±.02 [.51]  (XX = ±.005[.13]
3FKR5	VENSIONS SHO	UNLESS OTHERWISE SPECIF DIMENSIONS  TOLERANGES:  X = ± 2 [5.08] FRACTIONS  XX = ± .02 [.51] ± 1/32  XXX = ± .005[.13] ANGLES ± 1
K.DANG	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY	UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES    DIMENSIONS IN [] ARE MILLIMETERS   CABLE LENGTH (L) TOLERANCES:   L 12 (305] = +1 (251)     (= ±.0 [ [5.0]
ITEM NO. FMC./	NCE ONLY.	D LEADING DIMENSIONS ARE INCHES [] ARE MILLIMETERS  CABLE LENGTH (L) TOLERANGES:  L ≤ 12 [305] = +1 [25] / 0  12 [305] < L ≤ 100 [1624] = +2 [51] / 0  60 [1524] < L ≤ 120 [3048] = +4 [102] / 0  120 [3048] < L ≤ 300 [7620] = +6 [152] / 0  300 [7620] < L = +5%L / 0
FMCA2270	SCALE N	THIRDANGLE PROJECTION  THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF FAIRNEW MICROWAVE CORPORATION ALL RIGHTS RESERVED.  SHEET  1  OF 1
A REV	N/A	ROJECTION  THON AND DOCUMENT ERRY OF E CORPORATION. EESERVED. OF 1