





## ∅ 1.63[41.3] MOUNTING HOLE 1.38 MIN.

## NOTES:

CABLES 36" AND UNDER HAVE 1 LABEL CENTERED. CABLES OVER 36" HAVE 2 LABELS, ONE AT EACH END 6.0" FROM THE FRONT OF THE CONNECTOR.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.



III III III



⊳	SIZE		XX = ±		UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES	
3FKR5	CAGE CODE	ALL DIMENSIONS SH	X=±.2 [5.08] FRACTIONS .XX=±.02 [.51] ±1/32 60[1524] < L=120 .XXX=±.005[.13] ANGLES±1° 120 [3048] < L=120 .300 [76:			TOLERANCES:
MVEERAPPAN	DRAWN BY	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY				CABLE LENGTH (L) TOLERANCES:
FMCA2756	ITEM NO.	NCE ONLY.	L ≤ 12 [305] = +1 [25] / -0 12 [305] < L ≤ 60 [1624] = +2 [51] / -0 60 [1524] < L ≤ 120 [3048] = 4 [102] / -0 120 [3048] < L ≤ 300 [7620] = +6 [152] / -0 300 [7620] < L = +5%L / -0		L) TOLERANCES:	ONS ARE INCHES
		SCALE N	THE INFORMATION AND DESIGN IN THIS DOCUMENT OF FAIRVIEW MICROPOSATION ALL RIGHT'S RESERVED.  SHEET 1 0F 1			THRU ANGLE PROJECTION
⊳	REV	N/A	E CORPORATION. ESERVED. OF 1	TION AND DOCUMENT RTY OF CORPORATION. SERVED.		