



NOTES:
1. CABLES 36" AND UNDER HAVE 1 LABEL CENTERED.
CABLES OVER 36" HAVE 2 LABELS, ONE AT EACH END
6.0" FROM THE FRONT OF THE CONNECTOR.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES



TITLE

İ	SIZE		8.
			X = ±.2
	3FKR5	ALL DIME	UNLESS OTHERWISE    DIMEN
	R5	OHS SNOISI	WISE SPECIFIED DIMENSIONS INCES: FRACTIONS + 1/32 ANGLES ± 1°
	PSRINIVAS	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY	UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS  TOLERANCES:  CABLE LENGTH (L) TOLERANCES: L = 1.02 [5.08] FRACTIONS  (= ±.02 [5.1] ± 1/32 of 001 [524] < L ≤ 102 [504] = +2 [51] / -0 001 [524] < L ≤ 102 [0048] = +4 [102] / -0 001 [524] < L ≤ 300 [7620] = +6 [162] / -0 300 [7620] < L = +5%L / -0 300 [7620] < L = +5%L / -0
	ITEM NO. FMC/	NCE ONLY.	LEADING DIMENSIONS ARE INCHES    ARE MILLIMETERS    CABLE LENGTH (L) TOLERANCES:    L \( \) \( 21 \) 205   2 + 1   25   / 0 \)    12   305   \( L \) \( \) \( 60 \)   1524   - 2   51   / 0 \)    12   305   \( L \) \( \) \( 60 \)   1524   - 2   51   / 0 \)    13   300   7620   \( \) \( \) \( 60 \)   152   / 0 \)    20   3048   \( \) \( L \) \( \) \( 300 \)   7620   \( \)
	FMCA2831	SCALE N	THIRD-ANGLE PROJECTION  THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE REPORTERY OF FAIRNEMANICROWAVE CORPORATION ALL RIGHTS RESERVED.  SHEET  1  OF 1
	REV A	N/A	ION AND DOCUMENT OR AND CORPORATION. SERVED.  JF  1