



NOTES:
1. CABLES 36" AND UNDER HAVE 1 LABEL CENTERED.
CABLES OVER 36" HAVE 2 LABELS, ONE AT EACH END
6.0" FROM THE FRONT OF THE CONNECTOR.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS, DIVERSION CONTRARY TO U.S., LAW PROHIBITED.

ONLY



TITLE

A			× × × × × × × + + + + +		UNLE
CAGE CODE 3FK	ALL DIMI	X = ±.2 [5.08] FRACTIONS XX = ±.02 [.51] ±1/32 XXX = ±.005[.13] ANGLES ±1°		TOLERANCES:	SS OTHER
3FKR5	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY				UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS
YT.	NWO!	_			S IN [].
VTHAN	RE FO	0 [3048	12 [30 0 [1524	CABLE	EADING ARE MII
VTHANGARAJ	R REFE	120 [3048] < L ≤ 300 [7620] = +6 [152] / -0 300 [7620] < L = +5%L / -0	L ≤ 12 [305] = +1 [25] / -0 12 [305] < L ≤ 60 [1524] = +2 [51] / -0 60 [1524] < L ≤ 120 [3048] = +4 [102] / -0	CABLE LENGTH (L) TOLERANCES	LIMET
	RENC	[7620]	\$ 12 3 60 15 20 30	.(□) H	ISIONS
ITEM NO.	E ONL)	1 = 152] / L = 152] / 300 [7620] < L = 15%L / -0	L \(12 \] (305] = \(+1 \] (25] \(\) -0 \(\) \(60 \] (1524] = \(+2 \] (51] \(\) -0 \(\) \(120 \] (3048] = \(+4 \] (102] \(\) -	TOLER	ARE
	, , , , , , , , , , , , , , , , , , ,		1 [25] / 2 [51] / 4 [102]	ANCES	NCHES
/ICA		0 6 6 11			
FMCA3044	SCALE	SHEET	DESIGN IN THIS DOCUMENT IS THE PROPERTY OF FAIRVIEW MICROWAVE CORPORATIO ALL RIGHTS RESERVED.		4
		_	DESIGN IN THIS DOCUMENT IS THE PROPERTY OF IEW MICROWAVE CORPORA ALL RIGHTS RESERVED.	THE INFORMATION AND	THIRD-ANGLE PROJECTION
	N/A	유	SIGN IN THIS DOCUME IS THE PROPERTY OF W MICROWAVE CORPC ALL RIGHTS RESERVEI	ORMATI	₹ GEBW
REV	À	Ť	OCUME RTY OF CORPOI SERVED	S Z	7
P			NT SOLLY.		ž