





## NOTES:

CABLES 36" AND UNDER HAVE 1 LABEL CENTERED.
CABLES OVER 36" HAVE 2 LABELS, ONE AT EACH END
6.0" FROM THE FRONT OF THE CONNECTOR.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.



TIT IE

A		UNLESS OTHE  TOLER  X = ±.2 [5.08]  .X = ±.02 [.51]  .XX = ±.005[.13]
CAGE CODE 3FKR5	ALL DIME	UNLESS OTHERWISE    DIMEN   TOLERANCES   X = ±.2
R5	OHS SNOISN	WISE SPECIFI DIMENSIONS NICES: FRACTIONS ± 1/32 ANGLES ± 1°
VTHANGARAJ	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.	UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS  TOLERANCES:  CABLE LENGTH (1) TOLERANCES: L \$ 12 [508] FRACTIONS (= ±.02 [.51]
FMCA3088	NCE ONLY.	ADING DIMENSIONS ARE INCHES RE MILLIMETERS  2ABLE LENGTH (L.) TOLERANCES: L ≤ 12 [305] = +1 [25] / -0 12 [305] < L ≤ 60 [1824] = +2 [51] / -0 [1824] < L ≤ 120 [3048] = +4 [102] / -0 [3048] < L ≤ 300 [7820] < L = +6 [152] / -0 300 [7820] < L = +5%L / -0
\3088	SCALE Z	THIRD-ANGLE PROJECTION  THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE REPORTED TO ALL RIGHTS RESERVED.  SHEET  1  OF  1
A REV	N/A	EPROJECTION  AATION AND IS DOCUMENT PERTY OF PUE CORPORATION. RESERVED.  OF 1

A