


THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED. UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES



A		\text{VXX} = ±.
CAGE CODE 3FK	ALL DIM	UNLESS OTHERWISE; DIMEN TOLERANCES: X = ± 2 [5.08] FRAC XX = ± .02 [.5.1] ± XXX = ± .005[.13] ANGLESS
3FKR5	ENSIONS SH	ANCES: FRACTIONS ± 1/32 ANGLES ± 1°
BPUCHASKI	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY	 =
FMFX2025	NCE ONLY.	LEADING DIMENSIONS ARE INCHES ARE MILLIMETERS CABLE LENGTH (L) TOLERANCES: L ≤ 12 [306] = +1 [25] / -0 12 [305] < L ≤ 60 [1524] = +2 [51] / -0 60 [1524] < L ≤ 120 [3048] = +4 [102] / -0 120 [3048] < L ≤ 300 [7620] = +6 [152] / -0 300 [7620] < L = +5%L / -0
(2025	SCALE N	THIRD-ANGLE PROJECTION THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE EMPORERY OF FAIRWER WINDROWNAVE CORPORATION ALL RIGHTS RESERVED. SHEET 1 OF 1
REV A	N/A	ROJECTION TION AND DOCUMENT ERRY OF E CORPORATION. ESERVED. OF 1