









Pin 14 = +VCC
Pin 8 = Output
Pin 7 = TTL Option
All other Pins Ground

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.



TITLE

⊳	SIZE		XX X X X X X X X X X X X X X X X X X X	UNC
3FKR5	CAGE CODE	ALL DIM	TOLERANCES X = ±.2 [5.08] FRAC XX = ±.02 [.51] ± (XX = ±.005[.13] ANGI	UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS
		ENSIONS SHO	TOLERANCES: X = ±.2 [5.08] FRACTIONS XX = ±.02 [.51] ± 1/32 XXX = ±.005[.13] ANGLES ± 1°	
DZINN	DRAWN BY	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.		
FMNS5002	ITEM NO.		CABLE LENGTH (L) TOLERANCES: L ≤ 12 [305] = +1 [25] / 0 12 [305] < L ≤ 60 [1624] = +2 [51] / 0 60 [1524] < L ≤ 120 [3048] = +4 [102] / 0 120 [3048] < L ≤ 300 [7620] = +6 [152] / 0 300 [7620] < L = +5%L / 0	
5002		SCALE N	THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF FAIRNER MINORANGE CORPORATION ALL NIGHT'S RESERVED. SHEET 1 OF 1	THIRD-ANGLE PROJECTION
₿	REV	N/A	ATTION AND SOCUMENT OF AECORPORATION. RESERVED. OF 1	Z OFFICION