







THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.



TITLE



UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES    TOLERANCES:   CABLE LENGTH (L) TOLERANCES:   THE INFORMATION AND DESIGN IN THE INFORMATION AND DESIGN IN THE INFORMATION AND DESIGN IN THIS DOCUMENT     X = ±.2							
IED LEADING DIMENSIONS ARE INCHES   IN [] ARE MILLIMETERS     CABLE LENGTH (L) TOLERANCES:   L ≤ 12 [305] = +1 [25] / -0     12 [305] < L ≤ 60 [1624] = +2 [61] / -0     60 [1524] < L ≤ 120 [3048] = +4 [102] / -0     120 [3048] < L ≤ 120 [3048] = +6 [152] / -0     120 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [102] / -0     200 [3048] < L ≤ 120 [3048] = +6 [102] / -0     200 [3048] < L ≤ 120 [3048] = +6 [102] / -0     200 [3048] < L ≤ 120 [3048] = +6 [102] / -0     200 [3048] < L ≤ 120 [3048] = +6 [102] / -0     200 [3048] < L ≤ 120 [3048] = +6 [102] / -0     200 [3048] < L ≤ 120 [3048] = +6 [102] / -0     200 [3048] < L ≤ 120 [3048] = +6 [102] / -0     200 [3048] < L ≤ 120 [3048] = +6 [102] / -0     200 [3048] < L ≤ 120 [3048] = +6 [102] / -0     200 [3048] < L ≤ 120 [3048] = +6 [102] / -0     200 [3048] < L ≤ 120 [3048] = +6 [102] / -0     200 [3048] < L ≤ 120 [3048] = +6 [102] / -0     200 [3048] < L ≤ 120 [3048] = +6 [102] / -0     200	⊳	SIZE		L ≤ 12 [305] = +1 [25] / 0  12 [305] < L ≤ 60 [1524] = +2 [51] / 0  60 [1524] < L ≤ 120 [3048] = +4 [102] / 0  120 [3048] < L ≤ 300 [7620] = +6 [152] / 0  300 [7620] < L = +5%L / 0			CN
IED LEADING DIMENSIONS ARE INCHES   IN [] ARE MILLIMETERS     CABLE LENGTH (L) TOLERANCES:   L ≤ 12 [305] = +1 [25] / -0     12 [305] < L ≤ 60 [1624] = +2 [61] / -0     60 [1524] < L ≤ 120 [3048] = +4 [102] / -0     120 [3048] < L ≤ 120 [3048] = +6 [152] / -0     120 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [152] / -0     200 [3048] < L ≤ 120 [3048] = +6 [102] / -0     200 [3048] < L ≤ 120 [3048] = +6 [102] / -0     200 [3048] < L ≤ 120 [3048] = +6 [102] / -0     200 [3048] < L ≤ 120 [3048] = +6 [102] / -0     200 [3048] < L ≤ 120 [3048] = +6 [102] / -0     200 [3048] < L ≤ 120 [3048] = +6 [102] / -0     200 [3048] < L ≤ 120 [3048] = +6 [102] / -0     200 [3048] < L ≤ 120 [3048] = +6 [102] / -0     200 [3048] < L ≤ 120 [3048] = +6 [102] / -0     200 [3048] < L ≤ 120 [3048] = +6 [102] / -0     200 [3048] < L ≤ 120 [3048] = +6 [102] / -0     200 [3048] < L ≤ 120 [3048] = +6 [102] / -0     200 [3048] < L ≤ 120 [3048] = +6 [102] / -0     200 [3048] < L ≤ 120 [3048] = +6 [102] / -0     200	<u>ω</u>		ALL DIMENSIONS SHO			TOLER	ESS OTHER
0	KR5					ANCES:	DIMENSIONS
0	K.DANG	DRAWN BY	WN ARE FOR REFERE			CABLE LENGTH (	ED LEADING DIMENSIC IN [] ARE MILLIMETERS
THERD ANGLE PROJECTION  THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF FAIRWENMICHOWAVE CORPOPATION, ALL RIGHTS RESERVED.  SHEET  1  SCALE  N/A  SCALE  N/A  REV  A	FMWCA9871	ITEM NO.	NCE ONLY.			L) TOLERANCES:	ONS ARE INCHES
OLECTION  ON AND  ON OWNER  ON OWNER				SHEET 1 C	DESIGN IN THIS DESIGN IN THIS DESIGN IN THE PROPEI FAIRVIEW MICROWAVE ALL RIGHTS RE	THE INFORMATI	THIRD-ANGLE PR
	≻	REV	/A	1	ROCUMENT RTY OF CORPORATION. SERVED.	ON AND	OJECTION