





## LABEL:

PN: SA3N10W-06 SN: XXXXXXXX BIDIRECTIONAL ATTENUATOR 3GHz M/F 10 Watts 6dB

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.



⊳	0W-06	SA3N10W-06	K.DANG	3FKR5	3F	≻	
REV		ITEM NO.	DRAWN BY		CAGE CODE	SIZE	
N/A	SCALE N	NCE ONLY.	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY	ENSIONS SHO	ALL DIM		
OF <b>1</b>	SHEET 1	120 [3048] < L ≤ 300 [7620] = +6 [152] / -0 300 [7620] < L = +5%L / -0	120 [3048] < L ≤ 300 300 [76	() ()		300	
DOCUMENT RTY OF CORPORATION. SERVED.	DESIGN IN THIS DOCUMENT IS THE PROPERTY OF FAIRVIEW MICROWAVE CORPORATION ALL RIGHT'S RESERVED.	L \( \times 12 \) [305] = \( \times 1 \) [25] \( \times 0 \) 12 \( \times 305 \) \( \times 60 \) [1524] = \( \times 2 \) [51] \( \times 0 \) 60 \( \times 1524 \) \( \times 120 \) [3048] = \( \times 4 \) [102] \( \times 0 \)	L ≤ 1 12 [305] < L ≤ 60 60 [1524] < L ≤ 120	FRACTIONS ± 1/32 ANGLES + 1°	$X = \pm .2$ [5.08] $XX = \pm .02$ [.51] $XXX = \pm .005$ [.13]	.X = ±.2	
ION AND	THE INFORMATION AND	CABLE LENGTH (L) TOLERANCES:	CABLE LENGTH	NCES:	TOLERANCES:		
	HIRD-ANGLE PROJECTION	ONS ARE INCHES	UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES	DIMENSIONS	ESS OTHER	S.	