





THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.





⊳	SIZE		X = ±.2 [5.08] FRACTIONS XX = ±.02 [.51] ± 1/32 XXX = ±.005[.13] ANGLES ± 1°						UNL
ω	CAGE CODE	ALL DIMENSIONS SHO				0	1	SS OTHE	
3FKR5						ANCES:	TOLERANCES:		RWISE SPECIFIED LEADING DIMENSIO DIMENSIONS IN [] ARE MILLIMETERS
K.DANG	DRAWN BY	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.	_	L \(\le 12 \] [305] = +1 [25] / -0 12 [305] < L \(\le 60 \] [1524] = +2 [51] / -0 60 [1524] < L \(\le 120 \] [3048] = +4 [102] / -0		CABLE LENGIH	CABLE LENGTH (L) TOLERANCES		UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES
SPA-110-30-01-SMA	ITEM NO.	NCE ONLY.	120 [3048] < L ≤ 300 [7620] = +6 [152] / -0 300 [7620] < L = +5%L / -0	L ≤ 12 [305] = +1 [25] / -0	(L) TOLERANCES:		ONS ARE INCHES		
0-01-SMA		SCALE N	SHEET 1	THE INFORMA ESIGN IN THIS IS THE PROP WMICROWAV ALL RIGHTS F					
≻	REV	N/A	¥ 1	DOCUMENT ERTY OF E CORPORATION. ESERVED. OF 1				1	OJECTION