

## 30 dB Fixed Attenuator SMA Male (Plug) to SMA Female (Jack) Unidirectional Up to 12.4 GHz Rated to 10 Watts, Black Aluminum Body, 1.3:1 VSWR

Fairview Microwave carries a broad selection of fixed attenuators with a wide range of attenuation levels, frequency ranges, and power dissipation ranges. Also known as RF pads, RF microwave attenuators lower the amplitude of a signal (or attenuate) a known amount. These attenuator pads can be used in a wide variety of applications including reducing a signal level to protect measurement equipment or other circuitry, extending the range of power meters and amplifiers, and impedance matching circuits by reducing the VSWR seen by adjacent components. RF attenuators can prevent signal overload in amplifiers, receivers and detectors, adjusting the signal level to a range that is optimal.

Few RF components are as commonly used as fixed coaxial attenuators, and Fairview Microwave carries one of the largest in-stock varieties and ships them same day. The FMAT7463-30 is a 30 dB Fixed Attenuator that operates from DC to 12.4 GHz and is rated to 10 Watts. The versatile coaxial package uses SMA male to SMA female connectors and is also RoHS compliant.



### Features:

- DC to 12.4 GHz Frequency Range
- SMA Connectorized Design
- Attenuation 30 dB  $\pm$ 0.6 dB
- Max Power 10 Watts (CW)
- Max VSWR of 1.3:1

### Applications:

- Instrumentation
- Precision Measurements
- Prototyping and Characterization
- Production Systems
- WIFI 6E
- 5G Cellular Bands

### Electrical Specifications

Description	Min	Typ	Max	Units
Frequency Range	DC		12.4	GHz
Impedance		50		Ohms
Nominal Attenuation		30		dB
Attenuation Accuracy		0.6		dB
VSWR			1.3:1	
Input Power, CW Derated linearly to 1W at 125°C			10	Watts
Input Power, Peak 5 $\mu$ s pulse, 2% Duty Cycle			500	Watts

### Mechanical Specifications

Size	
Length	1.89 in [48.01 mm]
Width/Diameter	0.65 in [16.51 mm]
Weight	0.33 lbs [149.69 g]
Body Material and Plating	Black Anodized Aluminum

### Configuration

Design	Fixed, Unidirectional
--------	-----------------------

### Connectors

Description	Connector 1	Connector 2
Type	SMA Male	SMA Female
Contact Material & Plating	Brass, Gold	Beryllium Copper, Gold
Body Material & Plating	Brass, Nickel	Brass, Nickel

Fairview Microwave  
 301 Leora Ln., Suite 100  
 Lewisville, TX 75056  
 Tel: 1-800-715-4396 / (972) 649-6678  
 Fax: (972) 649-6689  
[www.fairviewmicrowave.com](http://www.fairviewmicrowave.com)  
[sales@fairviewmicrowave.com](mailto:sales@fairviewmicrowave.com)

## Environmental Specifications

### Temperature

Operating Range -55 to +125 deg C

**Compliance Certifications** (see [product page](#) for current document)

## Plotted and Other Data

Notes:

30 dB Fixed Attenuator SMA Male (Plug) to SMA Female (Jack) Unidirectional Up to 12.4 GHz Rated to 10 Watts, Black Aluminum Body, 1.3:1 VSWR from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [30 dB Fixed Attenuator SMA Male \(Plug\) to SMA Female \(Jack\) Unidirectional Up to 12.4 GHz Rated to 10 Watts, Black Aluminum Body, 1.3:1 VSWR FMAT7463-30](#)

URL: <https://www.fairviewmicrowave.com/30db-fixed-attenuator-sma-male-sma-female-10-watts-fmat7463-30-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.

