

3 dB RF Fixed Attenuator TNC Male (Plug) to TNC Female (Jack), DC to 3 GHz Rated to 2 Watt, Brass Body, 1.25:1 VSWR

FMAT7609-3

Features

- · DC to 3 GHz Range
- Attenuation 3 ±0.3 dB

Applications

- · Precision Measurements
- · Production Systems

- · 2 Watts (CW) Power
- VSWR <1.25:1
- Instrumentation
- · Prototyping and Characterization

Description

Fairview Microwave carries a wide range of fixed attenuators with a broad selection of attenuation levels, frequency ranges, and power dissipation ranges. RF microwave attenuators (also known as RF pads) lower the amplitude of a signal (attenuate) a known amount and can be used in a wide variety of applications. These attenuators pads are used when a signal needs to be reduced to protect measurement equipment or other circuitry, to extend the range of power meters and amplifiers, and to impedance match circuits by reducing the VSWR seen by adjacent components. RF attenuators can prevent signal overload in amplifiers, receivers and detectors, adjusting the signal level to a range that is optimal.

Few RF components are as commonly used as fixed coaxial attenuators, and Fairview Microwave carries one of the largest in-stock varieties and ships them same day. The 3 dB Fixed Attenuators FMAT7609-3 is rated to 2 Watts and operates from DC to 3 GHz. The versatile coaxial package uses TNC male to TNC female connectors.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		3	GHz
Impedance		50		Ohms
Nominal Attenuation		3		dB
Attenuation Accuracy		0.3		dB
VSWR			1.25:1	
Input Power, CW			2	Watts

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency Range	DC to 2	2 to 3				GHz
VSWR, Max	1.15:1	1.25:1				

Mechanical Specifications

Body Material and Plating

Size

 Length
 2.087 in [53.01 mm]

 Width/Diameter
 0.63 in [16 mm]

 Height
 0.63 in [16 mm]

 Weight
 0.1 lbs [45.36 g]

Brass, Copper-Tin-Zinc Alloy

Configuration

Design Fixed, Bidirectional



3 dB RF Fixed Attenuator TNC Male (Plug) to TNC Female (Jack), DC to 3 GHz Rated to 2 Watt, Brass Body, 1.25:1 VSWR



FMAT7609-3

Connectors

Description Connector 1		Connector 2		
Туре	TNC Male	TNC Female		
Contact Material and Plating	Phosphor Bronze, Gold	Phosphor Bronze, Gold		
Dielectric Type	Teflon	Teflon		
Body Material and Plating	Brass, Copper-Tin-Zinc Alloy	Brass, Copper-Tin-Zinc Alloy		

Environmental Specifications

Temperature

Operating Range

-50 to +85 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Typical Performance Data

3 dB RF Fixed Attenuator TNC Male (Plug) to TNC Female (Jack), DC to 3 GHz Rated to 2 Watt, Brass Body, 1.25:1 VSWR from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: 3 dB RF Fixed Attenuator TNC Male (Plug) to TNC Female (Jack), DC to 3 GHz Rated to 2 Watt, Brass Body, 1.25:1 VSWR FMAT7609-3

URL: https://www.fairviewmicrowave.com/3db-fixed-attenuator-tnc-male-tnc-female-2-watts-fmat7609-3-p.aspx

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume liability arising out of the use of any part or document.

FMAT7609-3 CAD Drawing

3 dB RF Fixed Attenuator TNC Male (Plug) to TNC Female (Jack), DC to 3 GHz Rated to 2 Watt, Brass Body, 1.25:1 VSWR

