

SMB Male Push-On Connector Solder Attachment For RG405 Cable

Electrical Specifications

Description	Min	Typ	Max	Units
Frequency Range	DC		4	GHz
VSWR			1.3:1	
Operating Voltage (AC)			335	Vrms

Mechanical Specifications

Size	Min	Typ	Max	Units
Length			0.533 in [13.54 mm]	
Width/Dia.			0.256 in [6.50 mm]	
Weight			0.006 lbs [2.72 g]	

Material Specifications

Description	Material	Plating
Contact	Beryllium Copper	Gold 30µ in. minimum
Insulation	PTFE	
Body	Brass	Gold 3µ in. minimum
Coupling Nut	Brass	Gold 3µ in. minimum

Environmental Specifications

Temperature	Min	Typ	Max	Units
Operating Range			-65 to 165	deg C

Compliance Certifications (visit www.FairviewMicrowave.com for current document)

RoHS Compliant	Yes
REACH Compliant	12/17/2015



Configuration:

- SMB Male Connector
- MIL-STD-348A
- 50 Ohms
- Straight Body Geometry
- RG405 Interface Type
- Solder/Solder Attachment

Fairview Microwave
 1130 Junction Dr. #100
 Allen, TX 75013
 Tel: 1-800-715-4396 / (972) 649-6678
 Fax: (972) 649-6689
www.fairviewmicrowave.com
sales@fairviewmicrowave.com

Plotted and Other Data


Notes:

SMB Male Push-On Connector Solder Attachment For RG405 Cable from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Allen, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [SMB Male Push-On Connector Solder Attachment For RG405 Cable FMC01045](#)

URL: <http://www.fairviewmicrowave.com/smb-male-push-on-rg405-connector-fmc01045-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.



ASSEMBLY PROCEDURES

1. STRIP THE CABLE TO THE DIMENSIONS SHOWN, DO NOT NICK CENTER CONDUCTOR OR METAL COVERING.
2. PUSH THE CENTER CONDUCTOR FULLY INTO THE CONTACT AND SOLDER, REMOVE EXCESS SOLDER.
3. PRESS CONTACT INTO BODY UNTIL IT SEATS.
4. SOLDER THE OUTER CONDUCTOR TO THE BODY STEM.

FAIRVIEW MICROWAVE INC. ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM		NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm].			
TITLE SMB Male Push-On Connector Solder Attachment For RG405 Cable		DWG NO FMC01045		CAGE CODE 3FKR5	
CAD FILE	102715	SHEET	SCALE	N/A	SIZE A 2233