

# RA SMA Male to RA MCX Plug Cable RG-188 Coax



### FMCA100093

### Configuration

Connector 1: SMA Male Right AngleConnector 2: MCX Plug Right Angle


Cable Type: RG-188Coax Flex Type: Flexible

#### **Features**

Max Frequency 3 GHz

PTFE Jacket





# **Applications**

· General Purpose

· Laboratory Use

### **Description**

The RA SMA male to RA MCX plug cable using RG188 coax, part number FMCA100093, from Fairview Microwave is in-stock and ships same day. This Fairview SMA to MCX cable assembly has a male to plug gender configuration with 50 ohm flexible RG-188 coax. Fairview Microwave's flexible RF cable assemblies are ideal for applications where tight bends and continual flexure are required. The FMCA100093 SMA male to MCX plug cable assembly operates to 3 GHz. The right angle SMA and right angle MCX interfaces on the RG-188 cable allow for easier connections in tight spaces.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other RF cable assembly value added services including connector orientation or clocking, heat shrink booting and labeling are also available. RF testing can also be performed to document the electrical performance of your cable assembly.

### **Electrical Specifications**

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		3	GHz
VSWR			1.4:1	

### **Mechanical Specifications**

**Cable Assembly** 

 Width/Diameter
 0.5 in [12.7 mm]

 Weight
 0.038 lbs [17.24 g]

Cable

Cable TypeRG-188Impedance50 OhmsInner Conductor TypeStranded

Inner Conductor Material and Plating Copper Clad Steel, Silver



# RA SMA Male to RA MCX Plug Cable RG-188 Coax



# FMCA100093

Dielectric Type Number of Shields Shield Layer 1 Jacket Material Jacket Diameter PTFE 1 Silver Plated Copper Braid PTFE, White 0.11 in [2.79 mm]

#### **Connectors**

Description	Connector 1	Connector 2	
Туре	SMA Male Right Angle	MCX Plug Right Angle	
Specification	MIL-STD-348A	MIL-STD-348A	
Impedance	50 Ohms	50 Ohms	
Configuration	Right Angle	Right Angle	
Contact Material and Plating	Brass, Gold	Brass, Gold	
Contact Plating Specification	50 μin minimum	30 μin minimum	
Dielectric Type	PTFE	PTFE	
Body Material and Plating	Brass, Nickel	Brass, Gold	
Body Plating Specification	100 μin minimum	3 μin minimum	
Coupling Nut Material and Plating	Brass, Nickel		
Coupling Nut Plating Specification	100 μin minimum		
Hex Size	5/16 inch		

# **Environmental Specifications**

Operating Range Temperature

-40 to +60 deg C

Compliance Certifications (see product page for current document)

#### **Plotted and Other Data**

Notes:




# RA SMA Male to RA MCX Plug Cable RG-188 Coax



# FMCA100093

### **Typical Performance Data**

#### **How to Order**



Example: FMCA100093-12 = 12 inches long cable

FMCA100093-100cm = 100 cm long cable

RA SMA Male to RA MCX Plug Cable RG-188 Coax from Fairview Microwave is in-stock and available to ship same-day. All of our RF/ microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF ondemand.

For additional information on this product, please click the following link: RA SMA Male to RA MCX Plug Cable RG-188 Coax FMCA100093

URL: https://www.fairviewmicrowave.com/ra-sma-male-to-ra-mcx-plug-cable-rg188-coax-fmca100093-p.aspx

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume liability arising out of the use of any part or document.

