



## 20KV Male to MHV Male Cable RG213HV Coax

The 20KV male to MHV male cable using RG213HV coax, part number FMCA9769, from Fairview Microwave is in-stock and ships same day. This Fairview 20KV to MHV cable assembly has a male to male gender configuration with 50 ohm RG213HV coax. Our 20kV high voltage RF cable assemblies are designed to handle higher voltages and minimize the risk of electric shock. Both the connectors used in this cable assemblies have recessed contact design to withstand unmated higher voltage. These cable assemblies are commonly used in applications where high voltage transmission and RF signal integrity are critical. These cable assemblies are constructed with high-quality insulation materials capable of withstanding higher voltages, ensuring safety and preventing electrical breakdown. Our cable assemblies are built with durable and flexible materials to withstand harsh environmental conditions and repetitive movements, ensuring reliable performance over extended periods.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other RF cable assembly value added services including connector orientation or clocking, heat shrink booting and labeling are also available. RF testing can also be performed to document the electrical performance of your cable assembly.

# **Electrical Specifications**

Description	Min	Т	ур	Max	U	nits
Velocity of Propagation		6	59			%
Operating Voltage (DC)				20,000	,	Vdc
Test Voltage (DC)				30,000		V

Electrical Specification Notes: Values at 25°C, sea level.

## **Mechanical Specifications**

### **Cable Assembly**

Weight 0.158 lbs [71.67 g]

#### Cable

Cable Type RG213HV
Impedance 50 Ohms
Inner Conductor Material and Plating Copper, Bare
Dielectric Type PE
Number of Shields 1

Jacket Material Polyurethane

Jacket Diameter 0.394 in [10.01 mm]

Repeated Minimum Bend Radius 1.969 in [50.01 mm]



# **Configuration:**

- 20KV Male
- MHV Male
- RG213HV

## **Features:**

- 69% Phase Velocity
- Polyurethane Jacket
- Voltage rating of 10kV
- Recessed Contacts

# **Applications:**

- General Purpose
- Laboratory Use
- High voltage power supplies/Amplifiers
- Nuclear instrumentation
- Test and measurement equipment

Fairview Microwave 301 Leora Ln., Suite 100 Lewisville, TX 75056 Tel: 1-800-715-4396 / (972) 649-6678 Fax: (972) 649-6689 www.fairviewmicrowave.com sales@fairviewmicrowave.com





### **Connectors**

Description	Connector 1	Connector 2		
Туре	20KV Male Bayonet	MHV Male Bayonet		
Specification	MIL-STD-202	MIL-STD-202		
Impedance	50 Ohms	50 Ohms		
Contact Material & Plating	Brass, Gold/Tri-Metal	Silver		
Contact Plating Spec.		QQ-S-365		
Dielectric Type	PE (HD)	PTFE		
Body Material & Plating	Brass, Tinned Copper	Brass, Nickel		
Body Plating Spec.		QQ-N-290		
Coupling Nut Material & Plating	Brass, Tinned Copper	Brass, Nickel		
Coupling Nut Plating Spec.		QQ-N-290		

**Compliance Certifications** (see product page for current document)

### **Plotted and Other Data**

Notes:

Values at 25°C, sea level.

#### **How to Order**

Part Number Configuration:



Example: FMCA9769-12 = 12 inches long cable

FMCA9769-100cm = 100 cm long cable

20KV Male to MHV Male Cable RG213HV Coax from Fairview Microwave has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link to obtain additional part information: 20KV Male to MHV Male Cable RG213HV Coax FMCA9769

URL: https://www.fairviewmicrowave.com/20kv-male-to-mhv-male-cable-rg213hv-coax-fmca9769-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.

301 Leora Ln., Suite 100, Lewisville, TX 75056 | Tel: 1-800-715-4396 / (972) 649-6678 / Fax: (972) 649-6689





