


RA BMMA Male (Plug) PCB Connector Thru Hole Solder Attachment 0.200 inch X 0.067 inch Hole Spacing



FMCN5140

Configuration

- BMMA Male Connector
- 50 Ohms
- Right Angle Body Geometry
- Connector Interface Types: Thru Hole

Features

- Operating Frequency of 26.5 GHz Max.
- Good VSWR of 1.45:1
- Gold Plated Beryllium Copper Contact

Applications

- General Purpose Test
- PCB Applications

Description

RA BMMA Male Standard Connector Solder Attachment for Thru hole Cable, part number FMCN5140, from Fairview Microwave is in-stock and ships same day. This BMMA male connector operates up to a maximum frequency of 26.5 GHz and offers good VSWR of 1.45:1. Its right angle body geometry facilitates connections in tight spaces.

Fairview's RA BMMA male connector FMCN5140 datasheet specifications and outline drawing are shown in this PDF below. Our extensive offering of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. From providing an I/O for a board design to creating a custom cable assembly configuration, Fairview Microwave has a connector solution to meet your needs. Fairview Microwave also has the expertise to build your custom cable assemblies for you and ship them same-day.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		26.5	GHz
VSWR			1.45:1	
Insertion Loss			0.772	dB
Impedance		50		Ohms

Mechanical Specifications


Size

Length	0.542 in [13.77 mm]
Width	0.24 in [6.1 mm]
Height	0.425 in [10.8 mm]
Weight	0.006 lbs [2.72 g]
Mating Cycles	500 Cycles

Material Specifications

Description	Material	Plating
Contact	Beryllium Copper	Gold
Insulation	PTFE	
Outer Conductor	Stainless Steel	Gold
Body	Stainless Steel	Gold

RA BMMA Male (Plug) PCB Connector Thru Hole Solder Attachment 0.200 inch X 0.067 inch Hole Spacing



FMCN5140

Environmental Specifications

Temperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

RA BMMA Male (Plug) PCB Connector Thru Hole Solder Attachment 0.200 inch X 0.067 inch Hole Spacing from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [RA BMMA Male \(Plug\) PCB Connector Thru Hole Solder Attachment 0.200 inch X 0.067 inch Hole Spacing FMCN5140](#)

URL: <https://www.fairviewmicrowave.com/bmma-male-pcb-connector-fmcn5140-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume liability arising out of the use of any part or document.

FMCN5140 CAD Drawing

RA BMMA Male (Plug) PCB Connector Thru Hole Solder Attachment 0.200 inch X 0.067 inch Hole Spacing

