

80 dB Gain Limiting Amplifier Operating From 2 GHz to 6 GHz with -61 to 10 dBm Pin, 15 dBm Psat and SMA

The SLA-060-80-40-SMA is a 2 to 6 GHz high gain wide-band coaxial limiting amplifier. The model operates with an input power range of -61 to +10 dBm and maintains a limited output of +15 dBm minimum. This amplifier offers a flat high 80 dB gain and a gain flatness of ± 3.0 dB independent of the input. This excellent technical performance is achieved through the use of hybrid MIC design and advanced GaAs PHEMT devices, and supplied the power typically from a +12V DC power supply. The connectorized SMA module includes built-in voltage regulation, bias sequencing, and reverse bias protection for added reliability. The module is hermetically sealed for extreme environmental conditions.

Electrical Specifications (TA = +25°C, DC Voltage = 12Volts, DC Current = 550mA)

Description	Min	Typ	Max	Unit
Frequency Range	2		6	GHz
Small Signal Gain	80			dB
Gain Flatness		± 3		dB
Input Power	-61		+10	dBm
Psat	+15			dBm
Psat Flatness			± 1	dB
Noise Figure			4	dB
Input VSWR		2:1		
Output VSWR		2:1		
Operating DC Voltage	11	12	13	Volts
Operating DC Current			550	mA
Operating Temperature Range	-30		+70	°C

Absolute Maximum Rating

Parameter	Rating	Units
Source Voltage	+15	Volts
RF input Power	+17	dBm
Operating Temperature (base-plate)	-30 to +70	°C
Storage Temperature	-55 to +85	°C



ESD Sensitive Material, Transport material in Approved ESD bags. Handle only in approved ESD Workstation.

Configuration

Connector 1 SMA Female
Connector 2 SMA Female

Compliance Certifications (visit www.FairviewMicrowave.com for current



Features:

- 2 GHz to 6 GHz Frequency Range
- Wide Input Dynamic Range: -61 to +10 dBm
- Psat: 15dBm Min.
- High Small Signal Gain: 80 dB Min.
- Gain Flatness: ± 3 dB max
- Noise Figure: 4 dB maximum
- VSWR (In/Out) 2:1
- 50 Ohm Input and Output Matched
- -30 to 70°C Operating Temperature
- Unconditionally Stable
- Regulated Supply & Bias Sequencing
- Hermetically Sealed Module
- Overvoltage External Protection for Easy Repair

Applications:

- 2 GHz to 6 GHz Frequency Range
- Wide Input Dynamic Range: -61 to +10 dBm
- Psat: 15dBm Min.
- High Small Signal Gain: 80 dB Min.
- Gain Flatness: ± 3 dB max
- Noise Figure: 4 dB maximum
- VSWR (In/Out) 2:1
- 50 Ohm Input and Output Matched
- -30 to 70°C Operating Temperature
- Unconditionally Stable
- Regulated Supply & Bias Sequencing
- Hermetically Sealed Module
- Overvoltage External Protection for Easy Repair

Fairview Microwave
1130 Junction Dr. #100
Allen, TX 75013
Tel: 1-800-715-4396 / (972) 649-6678
Fax: (972) 649-6689
www.fairviewmicrowave.com
sales@fairviewmicrowave.com



document)



Plotted and Other Data



Notes:

- Values at 25 °C, sea level
- ESD Sensitive Material, Transport material in Approved ESD bags. Handle only in approved ESD Workstation.
- Heat Sink Required for Proper Operation, Unit is cooled by conduction to heat sink.

Typical Performance Data








80 dB Gain Limiting Amplifier Operating From 2 GHz to 6 GHz with -61 to 10 dBm Pin, 15 dBm Psat and SMA from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Allen, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [80 dB Gain Limiting Amplifier Operating From 2 GHz to 6 GHz with -61 to 10 dBm Pin, 15 dBm Psat and SMA SLA-060-80-40-SMA](#)

URL: <http://www.fairviewmicrowave.com/80-db-gain-limiting-amplifier-2-6-ghz-sla-060-80-40-sma-p.asp>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.



NOTE:
 HEAT SINK REQUIRED FOR PROPER OPERATION,
 UNIT IS COOLED BY CONDUCTING TO HEAT SINK.

FAIRVIEW MICROWAVE INC.
 ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM

NOTES:
 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
 3. DIMENSIONS ARE IN INCHES [mm].

TITLE
 80 dB Gain Limiting Amplifier Operating From 2 GHz
 to 6 GHz with -61 to 10 dBm Pin, 15 dBm Psat and
 SMA

DWG NO SLA-060-80-40-SMA	CAGE CODE 3FKR5
CAD FILE 050914	SHEET
SCALE N/A	SIZE A 2233