

Low PIM TNC Male to TNC Male Adapter

Electrical Specifications

Frequency Range	DC to 6 GHz
Maximum VSWR	1.25:1
Maximum Passive Intermodulation (2 x 20 Watts)	-150 dBc

Mechanical Specifications

Size	
Length	1.31 in [33.27 mm]
Width	0.629 in [15.98 mm]
Weight	0.07055 lbs [32 g]

Connector 1

Type	TNC Male
Inner Conductor Material and Plating	Beryllium Copper, Silver
Coupling Nut Material and Plating	Brass, Tri-Metal
Hex Size	9/16 inch
Torque	6 in-lbs [0.68 Nm]
Body Material and Plating	Brass, Tri-Metal
Dielectric Type	PTFE

Connector 2

Type	TNC Male
Inner Conductor Material and Plating	Beryllium Copper, Silver
Coupling Nut Material and Plating	Brass, Tri-Metal
Hex Size	9/16 Inch
Torque	6 in-lbs [0.68 Nm]
Body Material and Plating	Brass, Tri-Metal
Dielectric Type	PTFE

Environmental Specifications

Temperature	
Operating Range	-45 to +125 deg C

Compliance Certifications (visit www.FairviewMicrowave.com for current document)

Plotted and Other Data

- Notes:
- Values at 25 °C, sea level



Features:

- Connector 1: TNC Male
- Impedance 1: 50 Ohms
- Connector 2: TNC Male
- Impedance 2: 50 Ohms
- Adapter Design: Low PIM
- Body Style: Straight
- Low PIM: -150 dBc

Fairview Microwave
 1130 Junction Dr. #100
 Allen, TX 75013
 Tel: 1-800-715-4396 / (972) 649-6678
 Fax: (972) 649-6689
www.fairviewmicrowave.com
sales@fairviewmicrowave.com

Typical Performance Data




Low PIM TNC Male to TNC Male Adapter from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Allen, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [Low PIM TNC Male to TNC Male Adapter SM4085](#)

URL: <http://www.fairviewmicrowave.com/low-pim-tnc-male-tnc-male-adapter-sm4085-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.



FAIRVIEW MICROWAVE INC. ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM		NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm].			
TITLE Low PIM TNC Male to TNC Male Adapter		DWG NO SM4085		CAGE CODE 3FKR5	
CAD FILE	111914	SHEET	SCALE	N/A	SIZE A 150