



N Female to QMA Female Adapter

Type N female to QMA female adapter part number SM5570 from Fairview Microwave is in-stock and ships same day. This Fairview type N to QMA adapter has a female to female gender configuration. SM5570 type N female to QMA female adapter operates to 6 GHz. The Fairview Microwave RF adapter provides excellent VSWR of 1.25:1 maximum.

RF adapters can be used to enable connections between two connector types that would otherwise not mate. Certain RF adapter configurations can also be used to protect connectors on expensive equipment where the number of connect and disconnect cycles is high. An RF, microwave, or millimeter wave adapter is connected to the equipment and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connnector savers. Fairview Microwave also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications

Description	Min	Тур	Max	Units
Frequency Range	DC		6	GHz
VSWR			1.25:1	

Electrical Specification Notes: Values at 25°C, sea level.

Mechanical Specifications

Size

Length

2.58 in [65.53 mm]

Weight

0.069 lbs [31.3 g]

Description	Connect	or 1	Connector 2
Туре	N Fema	ile	QMA Female
Polarity	Standa	rd	Standard
Interface Specification	MIL-STD-	348	MIL-STD-348
Mating Cycles	500		

Material Specifications

Description	Connector 1	Connector 2		
Туре	N Female	QMA Female		
Contact Material	Beryllium Copper	Beryllium Copper		
Contact Plating	Gold	Gold		
Contact Plating Spec.	MIL-G-45204	MIL-G-45204		
Insulation Material	PTFE	PTFE		
Outer Contact Material	Passivated Stainless Steel	Passivated Stainless Steel		

Environmental Specifications

Temperature

Operating Range

-55 to +110 deg C



Configuration:

- N Female Connector 1
- QMA Female Connector 2
- 50 Ohms
- Straight Body Geometry

Features:

- VSWR of 1.25:1 max up to 6 GHz
- N interface meets MIL-STD-348
- QMA interface meets MIL-STD-348
- Contact plating according to MIL-G-45204
- Gold Plated Beryllium Copper Contact

Applications:

- Enables Between Series Connections
- General Purpose Test

Fairview Microwave 1130 Junction Dr. #100 Allen, TX 75013

Tel: 1-800-715-4396 / (972) 649-6678

Fax: (972) 649-6689 www.fairviewmicrowave.com sales@fairviewmicrowave.com






Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Typical Performance Data



N Female to QMA Female Adapter from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Allen, Texas. Fairview Microwave is RF on-demand.


For additional information on this product, please click the following link: N Female to QMA Female Adapter SM5570

URL: https://www.fairviewmicrowave.com/n-female-qma-female-adapter-sm5570-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.







FAIRVIEW MICROWAVE INC. ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM	NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm].					
N Female to QMA Female Adapter	DWG NO SM5570			CAGE CODE 3FKR5		
	CAD FILE 080714	SHEET	SCAL	E N/A	SIZE A	xxxx