

# TNC Fixed Torque Wrench in Break-Over Type 9/16 inch Bit that is Pre-set to 6 in-lbs

Fairview's break-over style torque wrenches allow accurate mating force when assembling and disassembling a variety of RF coaxial connectors. The unique feature of break-over torque wrenches is that they will "break" at the pivot point once the preset torque value force is achieved, effectively preventing the user from over tightening the coupling nut on the connector. Our break-over torque wrenches are lab-quality tools made with a durable nickel-plated steel alloy wrench head connected to a light weight, red anodized aluminum handle. These RF torque wrenches are secured inside a latched and labeled wooden box for proper storage.

#### Configuration

Torque Type Design Type Hex Size Torque Setting Torque Accuracy Torque Accuracy Percentage

Weight Handle Color Wrench Head Material Wrench Head Plating Handle Material Fixed Break-Over 9/16 in 6 in-lbs [0.68 Nm] ±0.24 in-lbs [±0.03 Nm] ±4 %

0.482 lbs [218.63 g] Red Steel Nickel Red Anodized Aluminum

### Compliance Certifications (see product page for current document)

#### Notes:

- Do not use on damaged connectors.
- To improve performance of a wrench that hasn't been used recently, actuate the wrench by clicking the wrench head back and forth several times before use. This will spread the lubricant through the internal mechanism.
- Break-over type torque wrenches require smooth consistent application of force. Each torquing action should be completed within 2 seconds. Slower or faster torquing action will detract from accuracy.

TNC Fixed Torque Wrench in Break-Over Type 9/16 inch Bit that is Pre-set to 6 in-Ibs from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Allen, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: TNC Fixed Torque Wrench in Break-Over Type 9/16 inch Bit that is Pre-set to 6 in-Ibs ST-TNC-916-BO6

#### URL: https://www.fairviewmicrowave.com/tnc-torque-wrench-break-over-st-tnc-916-bo6-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.



ST-TNC-916-BO6



### **Features:**

- Designed for continual use
- Torque wrench will "break" at the pivot point once torque value force is achieved
- Designed to prevent over torque
- Each break-over torque wrench comes secured inside a labeled wooden box
- •


## **Applications:**

- Attaching Test Cables in Lab Environments
- Final production
  attachment of product
- Field install and testing applications
- Anytime accurate torque is needed while preventing over-torque

Fairview Microwave 301 Leora Ln., Suite 100 Lewisville, TX 75056 Tel: 1-800-715-4396 / (972) 649-6678 Fax: (972) 649-6689 www.fairviewmicrowave.com sales@fairviewmicrowave.com







301 Leora Ln., Suite 100, Lewisville, TX 75056 | Tel: 1-800-715-4396 / (972) 649-6678 / Fax: (972) 649-6689