

FM51242 DATA SHEET

Indoor DAS Ceiling Omni Antenna, 5 dBi, 617 MHz - 6000 MHz, 4 x 4.3-10 Female, Low PIM

Fairview Microwave's Indoor DAS Ceiling Omni Antenna FM51242 is in stock and ready to ship the same-day of order. The FM51242 indoor ceiling omni antenna comes with 6dBi gain and 4×4.3 -10 female connectors. This indoor DAS ceiling omni antenna has a wide band frequency range from 617MHz to 6000MHz. The 4 port capabilities increase the 5G data speeds up to 4×4.3 -10 female increases the throughput, data speeds, quality of connection and allows more users to connect to the antenna.

Our omni antenna specialists are ready and available to answer any questions you may have on the FM51242 indoor DAS ceiling omni antenna. The 6dBi ceiling omni antenna low profile designs allow for seamless installation indoors without creating eyesores or potential interference with indoor personnel. These low PIM antennas have low loss pigtails that allows for installation flexibility.

Contact Fairview Microwave's expert technical support for assistance with the indoor DAS ceiling omni antenna or any Antenna. Our knowledgeable sales team simplifies the purchasing process and ensures that your ceiling Omni antenna will be exact to specification.

The omni antenna FM51242 from Fairview Microwave provides a higher quality connection and improved longevity. Order your 4-port low PIM (low noise) Indoor DAS Ceiling Omni Antenna FM51242 from Fairview Microwave today. There is no MOQ (minimum order quantity) and the product ships same day from our warehouse.

Configuration

3	
Design	Ceiling
Gain	3 dBi
Polarization	Horizontal
Connector Type	4.3-10 Female
Interface 2	4.3-10 Female
Interface 3	4.3-10 Female
Interface 4	4.3-10 Female
Number of Ports	4

Electrical Specifications

Description	Min	Тур	Max	Units
Frequency Range	617		6,000	MHz
Input VSWR			1.8:1	
Impedance		50		Ohms
Gain	3		4.5	dBi
Input Power			50	Watts
Passive Intermodulation			-153	dBc
3rd order, 2 x 20 W				

Specifications by Frequency

Description	Band 1	Band 2	Band 3	Band 4	Band 5	Units
Range	0.617-0.69	80.698-0.96	1.695-2.7	3.3-4	4.8-6	GHz
Port to Port Isola	ation 17	17	20	30	30	dB



Features:

- Indoor distribution of 5G, LTE, GSM/CDMA
- In-building public or private networks
- LPWAN, LoRA, LTE-M, NB-IoT, IoT, M2M applications
- DAS (Distributed Antenna Systems)

Applications:

- Low Passive Intermodulation (PIM) <-153 dBc @ 2x20W
- Vertical Polarization
- Low return loss, stable performance
- 4 x 4.3-10 Female connector for long lasting consistent results
- Covers all sub 6 GHz 5G frequency bands including 600 MHz and extended CBRS
- 360 degree omnidirectional pattern

Fairview Microwave 301 Leora Ln., Suite 100 Lewisville, TX 75056 Tel: 1-800-715-4396 / (972) 649-6678 Fax: (972) 649-6689 www.fairviewmicrowave.com sales@fairviewmicrowave.com





Gain	3	3	4.5	4.5	4.5	dBi
Horiz. Beam Width	360	360	360	360	360	Degrees
Vert. Beam Width	360	360	360	360	360	Degrees
VSWR	1.8:1	1.8:1	1.8:1	1.8:1	1.8:1	

Mechanical Specifications

Radome Material ABS

Size

 Length
 14.1732 in [360 mm]

 Width
 14.1732 in [360 mm]

 Height
 0.944882 in [24 mm]

 Weight
 10.46 lbs [4.74 kg]

Environmental Specifications

Temperature

Operating Range -55 to +60 deg C

Humidity <95

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Indoor DAS Ceiling Omni Antenna, 5 dBi, 617 MHz - 6000 MHz, 4 x 4.3-10 Female, Low PIM from Fairview Microwave is instock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: Indoor DAS Ceiling Omni Antenna, 5 dBi, 617 MHz - 6000 MHz, 4 x 4.3-10 Female, Low PIM FM51242

URL: https://www.fairviewmicrowave.com/wide-band-antenna-6-dbi-4.3-10-female-fm51242-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.

301 Leora Ln., Suite 100, Lewisville, TX 75056 | Tel: 1-800-715-4396 / (972) 649-6678 / Fax: (972) 649-6689

Copyright © 2020

REV 1 Page 2 of 3





