

3.5-4 dBi Omni Antenna 2.4-2.5 GHz, 4.9-5.85 GHz, N Type Female Fiberglass Radome, 2:1 Max VSWR

The Fairview Microwave brand FM510M1001 is an economical yet high performance dual band omnidirectional antenna designed for operation in the 2.4 GHz and 4.9/5.8 GHz frequency bands. Compact and lightweight, these antennas are ideally suited multipoint applications where wide coverage is desired.

The FM510M1001 antennas feature an integral N-Female bulkhead type connector that can mount through the wall of an equipment enclosure. Also included is a mast mounting kit which consists of a heavy-duty steel bracket and a pair of U-bolts. This kit allows for installations on masts up to 2.0" in diameter. A vented end cap and drain holes in the base help prevent moisture build-up inside the antenna. These features allow the antenna to be mounted in up or down positions.

Configuration

Design	Omni
Gain	3.5 dBi
Polarization	Vertical
Connector Type	N Female
Number of Ports	1
Lightning Protection	DC Short

Electrical Specifications

Description	Min	Typ	Max	Units
Frequency Range	2,400		5,850	MHz
Input VSWR			2:1	
Impedance		50		Ohms
Input Power			50	Watts

Specifications by Frequency

Description	Band 1	Band 2	Band 3	Band 4	Band 5	Units
Range	2.4-2.5	4.9-5.85				GHz
Gain	3.5	4				dBi
Horiz. Beam Width	360					Degrees
Vert. Beam Width	55					Degrees
Max Input Power	50					Watts

Mechanical Specifications

Radome Material	Fiberglass
Size	
Base Diameter	1.27 in [32.26 mm]
Radome Diameter	0.75 in [19.05 mm]
Length	5.1 in [129.54 mm]
Width	1.3 in [33.02 mm]
Height	1.3 in [33.02 mm]
Mounting Mast Diameter	1.2 to 2 in [30.48 to 50.80 mm]
Weight	0.6 lbs [272.16 g]



Features:

- High performance in a compact lightweight design
- Durable UV-Stable fiberglass radome with vented end cap and drain holes in base
- All weather operation
- Integral N-Female connector
- Includes mast mounting kit

Applications:

- 2.4/4.9/5.1/5.3/5.4/5.8 GHz Wireless LAN systems
- IEEE 802.11a/b/g/n and 802.11ac compatible
- Homeland Security and Public Safety band
- WiMAX and WiFi applications
- Multipoint and mobile applications

Fairview Microwave
301 Leora Ln., Suite 100
Lewisville, TX 75056
Tel: 1-800-715-4396 / (972) 649-6678
Fax: (972) 649-6689
www.fairviewmicrowave.com
sales@fairviewmicrowave.com

Environmental Specifications

Temperature

Operating Range -40 to +85 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

3.5-4 dBi Omni Antenna 2.4-2.5 GHz, 4.9-5.85 GHz, N Type Female Fiberglass Radome, 2:1 Max VSWR from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [3.5-4 dBi Omni Antenna 2.4-2.5 GHz, 4.9-5.85 GHz, N Type Female Fiberglass Radome, 2:1 Max VSWR FM51OM1001](#)

URL: <https://www.fairviewmicrowave.com/3.5-dbi-omni-antenna-2.4-2.5-ghz-4.9-5.85-ghz-n-tyfm-female-2-1-max-vswr-fm51om1001-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.

