Fairview Microwave

FM9860B-10-CPRG DATA SHEET

an INFINIT[©] brand

WR-159 Waveguide Standard Gain Horn Antenna Operating From 4.9 GHz to 7.05 GHz With a Nominal 10 dBi Gain With CPRG Flange

WaveguidehornantennasFM9860B-10-CPRGfromFairviewMicrowaveisjustonepart in a large selection of our waveguide components. Fairview TAA Complaint waveguide horn antenna is manufactured with a WR-159 / R-58 / WG-13 waveguide size. Our WR-159 / R-58 / WG-13 waveguide horn antenna is constructed with a CPR-159G flange and built to precise RF wave waveguide horn antenna design specifications.

Fairview Microwave's WR-159 / R-58 / WG-13 waveguide antenna with CPR-159G flange from Fairview Microwave is a 10 dBi gain and in-stock now. Our WR-159 / R-58 / WG-13 , 10 dBi gain horn antenna has a minimum frequency of 4.9 (GHz) and a maximum frequency of 7.05 (GHz). This waveguide WR-159 / R-58 / WG-13 horn antenna is TAA complaint, which can be used for government and military purpose. FM9860B-10-CPRG horn antenna flange has EIA / IEC / UK designation WR-159 / R-58 / WG-13 respectively. This Antenna is ideal for measurement standard and calibration application. The Grooved design in CPR flange allows for tight pressurized fitting with no leaks.

Additional specs on this Waveguide horn with WR-159 / R-58 / WG-13 can be found on the datasheet specifications above. This Waveguide antenna is part of over one million RF, microwave, and millimeter wave components in stock. Our part number FM9860B-10-CPRG Wave guide horn antenna is ready for same day purchase and shipping worldwide. Fairview also stocks a wide array of other waveguide products that ship same-day from our Lewisville, TX United States warehouse for all your RF/microwave and millimeter wave waveguide component needs.

Configuration

Design	WR-159 Standard Gain Horn
Pattern	Directional
Polarization	Linear

Electrical Specifications

Description	Min	Тур	Мах	Units
Frequency Range	4.9		7.05	GHz
Nominal Gain		10		dBi
VSWR		1.5:1		

Mechanical Specifications

Size	
Length	3.19 in [81.03 mm]
Width/Diameter	2.44 in [61.98 mm]
Height	4.24 in [107.7 mm]
Weight	0.172 lbs [78.02 g]

Waveguide Interface

Waveguide Size Flange Type Body Material and Plating WR-159 CPRG Aluminum



Features:

- WR-159 / R-58 / WG-13 Rectangular waveguide interface with 10 dBi Nominal Gain
- 4.9 GHz to 7.05 GHz
 Frequency range
- CPR-G (Grooved) flange
- Made from high-grade aluminum with corrosion resistant powder coating
- Consistent gain versus frequency
- TAA Compliant waveguides

Applications:

- TAA Compliant waveguides (Made in USA)
- Typical low VSWR < 1.5
- Antenna measurements
- Microwave Radio systems solutions
- Wireless communications
- Radome, Automotive antenna, Satellite antenna testing
- Laboratory use

Fairview Microwave 301 Leora Ln., Suite 100 Lewisville, TX 75056 Tel: 1-800-715-4396 / (972) 649-6678 Fax: (972) 649-6689 www.fairviewmicrowave.com sales@fairviewmicrowave.com

REV 1 Page 1 of 3 Copyright © 2020 an INFINIT[®] brand



Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

WR-159 Waveguide Standard Gain Horn Antenna Operating From 4.9 GHz to 7.05 GHz With a Nominal 10 dBi Gain With CPRG Flange from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: WR-159 Waveguide Standard Gain Horn Antenna Operating From 4.9 GHz to 7.05 GHz With a Nominal 10 dBi Gain With CPRG Flange FM9860B-10-CPRG

URL:

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.





301 Leora Ln., Suite 100, Lewisville, TX 75056 | Tel: 1-800-715-4396 / (972) 649-6678 / Fax: (972) 649-6689

Fairview Microwave



	DEVICIONO
	A INITIAL RELEASE 12/02/22 KHIETP/
CPR 159G AL MB R.31 (7.9) (4.24±.03 (107.7±0.8) (6.4) (6.4) (6.4) (6.4) (81.0) (81.0) (81.0) (40.4) (40.4) (6.4) (7.9) (40.4) (7.9) (40.4) (6.4) (7.9) (40.4) (6.4) (7.9) (40.4) (6.4) (7.9) (40.4) (6.4) (7.9) (40.4) (7.9) (40.4) (7.5) (1.7) (1.9)	$2.80\pm.03 \\ \hline [71.1\pm0.8] \\ 2.07\pm.03 \\ \hline [52.5\pm0.8] \\ \hline [1.6] \\ \hline \hline \hline [1.6] \\ \hline \hline [1.6] \\ \hline \hline \hline [1.6] \\ \hline \hline \hline \hline [1.6] \\ \hline $
NOTES: 1. LABEL PER ILS-100-03 (FOR INTERNAL USE ONLY). LABEL LOCATION SHOWN IS FOR REFERENCE ONLY. REGULATORY COMPLIANCE: EU ROHS DIRECTIVE (MOST RECENT RELEASED VERSION) THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTE ADMINISTRATION REGULATIONS. DIVERSIO	IN CONTRARY TO U.S. LAW PROHIBITED. UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES <u>DIMENSIONS IN [] ARE MILLIMETERS</u> <u>TOLERANCES:</u> <u>CABLE LENGTH (L) TOLERANCES:</u> L \$ 12 [305] = +1 [25] /-0 <u>THE INFORMATION AND</u> <u>CONTRACT</u>
WR-159 Waveguide Standard Gain Horn Antenna	XX = ±.02 [51] ±.132 (12) [52] L ≤ 300 [152] = 2 [51] -0 FAIRVEEW MICROWAVE CORPORAT ALL Right Reserved. XXX = ±.005 [.13] ANGLES ± 1° 120 [3048] < 4 L (2021) < -0
ITLE	.XX = 1.02 [51] ±132 60 [524] < L ≤ 102

301 Leora Ln., Suite 100, Lewisville, TX 75056 | Tel: 1-800-715-4396 / (972) 649-6678 / Fax: (972) 649-6689