

FMCA2683-50CM DATA SHEET

TNC Male Right Angle to BNC Male Cable in 50 CM Length Using RG223 Coax

The RA TNC male to BNC male cable using RG223 coax, part number FMCA2683-50CM, from Fairview Microwave is in-stock and ships same day. This Fairview TNC to BNC cable assembly has a male to male gender configuration with 50 ohm flexible RG223 coax. Fairview Microwave's flexible RF cable assemblies are ideal for applications where tight bends and continual flexure are required. The FMCA2683-50CM TNC male to BNC male cable assembly operates to 3 GHz. The right angle TNC interface on the RG223 cable allows for easier connections in tight spaces. The double shielding of this Fairview cable assembly provides excellent shielding effectiveness.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other RF cable assembly value added services including connector orientation or clocking, heat shrink booting and labeling are also available. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Min	Т	ур	Max	Units
Frequency Range	DC			3	GHz
Velocity of Propagation		6	66		%
Capacitance		30.8 [101.05]	pF/ft [pF/m]
Operating Voltage (AC)				500	Vrms

Performance by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	0.1	0.25	0.5	1	3	GHz
Insertion Loss (Typ.)	0.37	0.41	0.45	0.52	0.71	dB/ft
	1.21	1.35	1.48	1.71	2.33	dB/m

Electrical Specification Notes:

The Insertion Loss data above is based on the performance specifications of the coax cable and connectors used in this assembly. The Insertion Loss includes an estimated insertion loss of 0.1 dB for the straight connector and 0.2 dB for the right angle connector.

Mechanical Specifications

Cable Assembly

Length* 19.68 in [499.87 mm] Weight 0.1009 lbs [45.77 g]

Cable

Cable Type RG223
Impedance 50 Ohms
Inner Conductor Type Solid
Inner Conductor Material and Plating
Dielectric Type PE
Number of Shields 2



Configuration:

- TNC Male Right Angle
- BNC Male
- RG223

Features:

- Max Frequency 3 GHz
- 66% Phase Velocity
- Double Shielded
- PVC Jacket

Applications:

- General Purpose
- · Laboratory Use

Fairview Microwave 301 Leora Ln., Suite 100 Lewisville, TX 75056 Tel: 1-800-715-4396 / (972) 649-6678 Fax: (972) 649-6689

www.fairviewmicrowave.com sales@fairviewmicrowave.com





Shield Layer 1 Shield Layer 2 Jacket Material Jacket Diameter Silver Plated Copper Braid Silver Plated Copper Braid

PVC, Black

0.21 in [5.33 mm]

One Time Minimum Bend Radius

1 in [25.4 mm]

Connectors

Description	Connector 1	Connector 2			
Туре	TNC Male	BNC Male			
Specification	MIL-STD-348A	MIL-STD-348A			
Impedance	50 Ohms	50 Ohms			
Contact Material & Plating	Brass, Gold	Brass, Gold			
Contact Plating Spec.	30μ in. minimum	30µ in. minimum			
Dielectric Type	Teflon	Teflon			
Body Material & Plating	Brass, Nickel	Brass, Nickel			
Body Plating Spec.	100μ in. minimum	100µ in. minimum			
Coupling Nut Material & Pla	ating Brass, Nickel				
Coupling Nut Plating Spec.	100µ in. minimum				

Compliance Certifications (see product page for current document)

FMCA2683-100cm = 100 cm long cable

Plotted and Other Data

Notes:

• Values at 25°C, sea level.

How to Order

Part Number Configuration:

FMCA2683 - xx | uu | cm = Centimeters | chlank > = Inches | Length |

Example: FMCA2683-12 = 12 inches long cable

301 Leora Ln., Suite 100, Lewisville, TX 75056 | Tel: 1-800-715-4396 / (972) 649-6678 / Fax: (972) 649-6689





TNC Male Right Angle to BNC Male Cable in 50 CM Length Using RG223 Coax from Fairview Microwave has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link to obtain additional part information: TNC Male Right Angle to BNC Male Cable in 50 CM Length Using RG223 Coax FMCA2683-50CM

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order

URL: https://www.fairviewmicrowave.com/ra-tnc-male-to-bnc-male-cable-rg223-coax-in-50-cm-and-rohs-fmca2683-50cm-p.aspx

	ent improve													
	specificatio													
	of the part					r purpose	, and Fair	view N	1icrowav	e does	not as	sume a	ny liabili	ty.
arising ou	t of the use	of any p	part or do	ocument	tation.									





