

FMCA2732-50CM **DATA SHEET**

SMA Male to TNC Female Bulkhead Cable in 50 CM **Length Using RG223 Coax**

The SMA male to TNC female bulkhead cable using RG223 coax, part number FMCA2732-50CM, from Fairview Microwave is in-stock and ships same day. This Fairview SMA to TNC cable assembly has a male to female gender configuration with 50 ohm flexible RG223 coax. Fairview Microwave's flexible RF cable assemblies are ideal for applications where tight bends and continual flexure are required. Our RF cable assembly with TNC bulkhead interface allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications. The double shielding of this Fairview cable assembly provides excellent shielding effectiveness.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other RF cable assembly value added services including connector orientation or clocking, heat shrink booting and labeling are also available. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Min	Тур	Max	Units
Velocity of Propagation		66		%
Capacitance		30.8 [101.05]	pl	/ft [pF/m]

Mechanical Specifications

Cable Assembly

Length* 19.68 in [499.87 mm] Weiaht 0.1129 lbs [51.21 g]

Cable Cable Type

Impedance Inner Conductor Type Inner Conductor Material and Plating Dielectric Type Number of Shields Shield Layer 1 Shield Layer 2

Jacket Material Jacket Diameter

One Time Minimum Bend Radius

RG223 50 Ohms Solid

Copper, Silver

PΕ 2

> Silver Plated Copper Braid Silver Plated Copper Braid

PVC, Black

0.21 in [5.33 mm]

1 in [25.4 mm]

Fairview Microwave 301 Leora Ln., Suite 100

Lewisville, TX 75056 Tel: 1-800-715-4396 / (972) 649-6678

Fax: (972) 649-6689 www.fairviewmicrowave.com sales@fairviewmicrowave.com



Configuration:

- SMA Male
- TNC Female Bulkhead
- RG223

Features:

- 66% Phase Velocity
- Double Shielded
- PVC Jacket

Applications:

- General Purpose
- · Laboratory Use





Connectors

Description	Connector 1	Connector 2
Туре	SMA Male	TNC Female
Mount Method		Bulkhead
Specification	MIL-STD-348A	
Impedance	50 Ohms	50 Ohms
Contact Material & Plating	Brass, Gold	
Contact Plating Spec.	50µ in. minimum	
Dielectric Type	Teflon	
Body Material & Plating	Brass, Nickel	Brass, Nickel
Body Plating Spec.	100µ in. minimum	
Hex Size	5/16 in	
Torque	5 in-lbs 0.57 Nm	

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Values at 25°C, sea level.

How to Order

Part Number Configuration:

FMCA2732 - xx uu | cm = Centimeters | chlank > = Inches | Length

Example: FMCA2732-12 = 12 inches long cable

FMCA2732-100cm = 100 cm long cable

SMA Male to TNC Female Bulkhead Cable in 50 CM Length Using RG223 Coax from Fairview Microwave has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link to obtain additional part information: SMA Male to TNC Female Bulkhead Cable in 50 CM Length Using RG223 Coax FMCA2732-50CM

URL: https://www.fairviewmicrowave.com/sma-male-to-tnc-female-bulkhead-cable-rg223-coax-in-50-cm-and-rohs-fm-ca2732-50cm-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.

301 Leora Ln., Suite 100, Lewisville, TX 75056 | Tel: 1-800-715-4396 / (972) 649-6678 / Fax: (972) 649-6689





