

FMWCA1106 DATA SHEET

WR-112 to SMA Female End Launch Waveguide to Coax Adapter UBR84 with 6.57 GHz to 9.99 GHz in Aluminum

The FMWCA1106 is an end launch waveguide to coaxial adapter operating at a frequency range of 6.57 GHz to 9.99 GHz. This adapter offers a WR-112 waveguide interface size coupled with a precision tolerance UBR84 flange. The FMWCA1106 is constructed of aluminum and painted gray to ensure durability. The coaxial connector offered by this adapter uses an SMA Female connector.

Configuration

Waveguide Size WR-112
Flange UBR84
RF Connector SMA Female
Body Geometry End Launch

Electrical Specifications

Description	Min	Тур	Max	Units		
Frequency Range	6.57		9.99	GHz		
VSWR			1.25:1			
Insertion Loss			0.2	dB		
Input Power (CW)			50	Watts		

Mechanical Specifications

Size

 Length
 1.95 in [49.53 mm]

 Width
 1.88 in [47.75 mm]

 Height
 1.88 in [47.75 mm]

RF Connector

Connector Type SMA Female

Waveguide Interface

Waveguide Type WR-112
Flange Type UBR84
Body Material and Plating Aluminum

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Values at +25 °C, sea level unless stated otherwise



Features:

- 6.57 to 9.99 GHz Frequency Range
- WR-112 Waveguide Interface
- UBR84 Flange
- SMA Female RF Interface
- Comprenhensive waveguide offering also include E-Bends, H-Bends, Sections, Filters, Terminations, Couplers, and more.

Applications:

- Test Benches
- Radar
- Satellite
- · Microwave Radio Systems
- Military and Space
- Communication Systems

Fairview Microwave 301 Leora Ln., Suite 100 Lewisville, TX 75056 Tel: 1-800-715-4396 / (972) 649-6678 Fax: (972) 649-6689 www.fairviewmicrowave.com sales@fairviewmicrowave.com





WR-112 to SMA Female End Launch Waveguide to Coax Adapter UBR84 with 6.57 GHz to 9.99 GHz in Aluminum from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: WR-112 to SMA Female End Launch Waveguide to Coax Adapter UBR84 with 6.57 GHz to 9.99 GHz in Aluminum FMWCA1106

URL: https://www.fairviewmicrowave.com/wr112-sma-female-end-launch-waveguide-coax-adapter-ubr84-fmwca1106-p. aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order

to implem	ent improvements	. Fairview	Microw	ave reserve	s the righ	t to mak	e such	changes	as requ	ired. Unle	ss oth	nerwise
	specifications are											
suitability	of the part describ	bed hereir	for any	/ particular	purpose,	and Fair	view M	icrowave	does n	ot assume	any	liability
arising ou	t of the use of any	part or do	cument	ation.								





