



Inner DC Block From 10 MHz to 40 GHz With 2.92mm **Connectors**

Electrical Specifications

Description	Min	Тур	Max	Units		
Frequency Range	0.01		40	GHz		
Impedance		50		Ohms		
VSWR	1.45:1					
Insertion Loss		0.75		dB		
Operating Voltage (DC)			200	Volts		



Mechanical Specifications

Size Length 0.855 in [21.72 mm] Width 0.312 in [7.92 mm] Weight 0.0138 lbs [6.26 g]

Configuration Inner DC Block Design Package Type Connectorized

Description	Connector 1	Connector 2			
Туре	2.92mm Male	2.92mm Female			
Hex Size	5/16 Inch				


Compliance Certifications (visit www.FairviewMicrowave.com for current document)

REACH Compliant 12/17/2015

Plotted and Other Data

Notes:

Typical Performance Data



Fairview Microwave 1130 Junction Dr. #100 Allen, TX 75013

Tel: 1-800-715-4396 / (972) 649-6678

Fax: (972) 649-6689 www.fairviewmicrowave.com sales@fairviewmicrowave.com





Inner DC Block From 10 MHz to 40 GHz With 2.92mm Connectors from Fairview Microwave has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link to obtain additional part information: Inner DC Block From 10 MHz to 40 GHz With 2.92mm Connectors SD3476

URL: https://www.fairviewmicrowave.com/inner-dc-block-10-mhz-40-ghz-2.92mm-connectors-sd3476-p.aspx









STANDARD TOLERANCES

.X ±0.2 .XX ±0.1 .XXX ±0.05

*STANDARD TOLERANCES APPLY ONLY TO DIMENSIONS IN INCHES

FAIRVIEW MICROWAVE INC. ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM	NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm].					
Inner DC Block From 10 MHz to 40 GHz With 2.92mm Connectors	DWG NO SD3476			CAGE CODE 3FKR5		
	CAD FILE 070716	SHEET	SCAL	E N/A	SIZE A	2233